

daA1600-60lm - Basler dart

The Basler daA1600-60lm BCON camera with the e2v EV76C570 CMOS sensor delivers 60 frames per second at 2 MP resolution.



Number

1

+
-

Buy now or add to request cart

Request test camera



Add to watch list ☆

Specifications

General Information

Order Number	No-Mount: 107110, CS-Mount: 107111, S-Mount: 107112
--------------	---

Sensor

Sensor Vendor	e2v
Sensor	EV76C570
Shutter	Global Shutter
Max. Image Circle	1/1.8"
Sensor Type	CMOS
Sensor Size	7.2 mm x 5.4 mm
Resolution (HxV)	1600 px x 1200 px
Resolution	2 MP
Pixel Size (H x V)	4.5 µm x 4.5 µm
Frame Rate	60 fps
Mono/Color	Mono

Camera Data

Interface	BCON for LVDS
Pixel Bit Depth	8, 12 bits
Synchronization	<div><div>■</div> hardware trigger</div> <div><div>■</div> free-run</div> <div><div>■</div> software trigger</div>
Exposure Control	<div><div>■</div> programmable via the camera API</div>
Digital Input	1
Digital Output	2 l

Camera Data

Power Requirements	<ul style="list-style-type: none">5V DC (via BCON for LVDS interface)
Power Consumption (typical)	1.3 W

Housing

Housing Type	Board Level
Housing Size (L x W x H)	5.9 mm x 27 mm x 27 mm
Lens Mount	<ul style="list-style-type: none">CS-mountnoneS-mount
Housing Temperature	0 - 50°C
Weight (typical)	15g

Conformity

Conformity	<ul style="list-style-type: none">CERoHSFCCGenICamUL
------------	--

Features

Features

Click on a feature to open the corresponding topic in the Basler Product Documentation.

Color Creation and Enhancement	<ul style="list-style-type: none">Auto Function Profile: Anti-FlickerBacklight CompensationContrast Enhancement
I/O Control and Line Source Signals	<ul style="list-style-type: none">Acquisition Trigger Wait / Frame Burst Trigger WaitDebouncerExposure ActiveFlash WindowFrame Trigger WaitMinimum Output Pulse WidthTimer ActiveUser Output
Image Acquisition Control	<ul style="list-style-type: none">Acquisition StatusFrame Start TriggerTriggered by HardwareTriggered by Software
Miscellaneous	<ul style="list-style-type: none">Device Information ParametersUser Defined ValuesUser Sets (Configuration Sets)
Pixel Formats	<ul style="list-style-type: none">Mono 12Mono 8
Standard Features	<ul style="list-style-type: none">Auto Function ProfileBinning HorizontalBinning VerticalBlack LevelExposure AutoExposure Mode: Timed (Control via API)Gain

Features

Click on a feature to open the corresponding topic in the Basler Product Documentation.


- [Gain Auto](#)
- [Gamma Correction](#)
- [Region of Interest \(ROI\)](#)
- [Reverse X \(Horizontal Mirroring\)](#)
- [Reverse Y \(Vertical Mirroring\)](#)
- [Test Images](#)

Dimensions

Mechanical drawing for daA1600-60lm

Mechanical drawings provide the detailed measurements of a camera product. Click on the link below to download the mechanical drawing for daA1600-60lm.

[Download now](#)



share



tweet



share



share



mail



eNewsletter

Regular updates on events and product innovations:



Subscribe

Basler on the social networks

Keep in touch with us via the social networks:



