







## Communication Technologies

**Products** 

Solutions by Network Documents & Resources

Support

Where to Buy

**Contact Us** 

<u>United States</u> > <u>Electronics</u> > <u>Communication Technologies</u> > <u>Communication Technologies Product Catalog</u> > <u>Copper Connectors and Splices</u> > <u>United States</u> > <u>Electronics</u> > <u>Communication Technologies</u> > <u>Comm</u>

## 3M™ 710 25-Pair Bridge Splice Connectors Filled

3M ID 80611047657 UPC# 00051138784522 Part Number 3M710-BC1-25







3M™ 710 Bridge Splice Connector can be used with either straight-only connectors or straight/half-tap connectors to allow pluggable, 3-way splices, 25 pairs at a time.

3M™ 710 Bridge Splice Connector is made from flameretardant, engineering-grade plastic. This connector has a moisture-resistant compound that fills all voids to eliminate air or moisture pockets while maximizing the space constraints. It is designed for aerial, underground or buried applications in an outside plant, or for making connections in central office mainframe distribution systems in an approved enclosure.

- For PIC insulated conductors
- · Accommodates 26 to 22 AWG conductor sizes
- Sealed closure
- Connector with filled composition
- 384/pack



Questions? We can help Contact Us



**Documents** 

## **Specifications**

Cable Type	PIC
Closure Type	Sealed
Composition	Filled
Connector Pair Count	25 pair
Connector Type	Bridge
Flame Retardant	No
Modular Type	710
Product Type	Module
RUS Listed	Yes/BA
Solution for	Access Network: FTTH/FTTB/CATV, Access Network: xDSL, Wireless Network: Backhaul, Long-haul/Metro Loop Network: Outdoor
Wire Gauge	26 - 22 AWG

3M Communication Technologies: Connect to MyTelecom | Where to Buy | Contact Us | View Mobile Site

3M: News | Careers | Partners & Suppliers | Investor Relations | SDS Search | Transport Information Search | Help Center

<u>Legal Information</u> <u>Privacy Policy</u>

© 3M 2017. All Rights Reserved.