



+ CONNECTORS

TRANSISTOR SOCKETS



✓ Active

TE CONNECTIVITY (TE)
8080-1G7=2 SOLDER TAB ASSY

Augat | AD

8080-1G7
TE Internal Number: 5-1437504-3

Not EU RoHS Compliant
Not EU ELV Compliant

Number of Positions 3

Package TO-3

Lead Size Accepted 1.02 mm [.04 in]

Termination Method Solder

Operating Temperature Range (°C) -55 – 125

↓ PRODUCT DRAWING
English

↓ 3D PDF

DOCUMENTATION

Product Drawings

TRANSISTOR SOCKET

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Terminal Configuration Contact

Package TO-3

Product Type Socket

Configuration Features

Number of Positions 3

Number of Solder Lugs 2

Body Features

Lead Size Accepted 1.02 mm [.04 in]

Color Green or Blue

Insulator Material Phenolic

Contact Features

Terminal Plating Gold

Termination Method Solder

Pin Diameter (in) .04

Terminal Material Beryllium Copper

Socket Type Transistor

Usage Conditions

Operating Temperature Range (°C) -55 – 125

Industry Standards

Insulator Flammability Rating UL 94V-0

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF

