



Industrial Adhesives & Tapes

[United States](#) > [All 3M Products](#) > [Manufacturing](#) > [Industrial Adhesives & Tapes](#) > [Adhesives - Wind](#) > 3M™ Hot Melt Adhesive 3779 Q Amber, 5/8 in x 8 in, 11 lb per case

3M™ Hot Melt Adhesive 3779 Q Amber, 5/8 in x 8 in, 11 lb per case

3M ID 62377991328 UPC# 00021200857997 Part Number 3779Q 3M Product Number 3779

Print

Share



3M™ Hot Melt Adhesive 3779 Q is a 100% solids thermoplastic, high heat resistant adhesive. Good electrical properties for potting and wire tacking. UL 94 V-0 Listing.

- High heat resistance
- Excellent resistance to solids and oils.
- 100 percent solids
- Woodworking, furniture, automotive, transportation, aerospace, general industrial, upholstery, point of purchase display, sample boards, military, window, door, building, trophies, novelties, audio components, cabinets, construction, packaging, electronic
- Assembly, assembling joining, attaching, securing, repairing, potting, panel bonding, wire tacking, bundling, sealing, encapsulating, rigidizing, foam bonding, gluing, packaging, adhering, and closing.

Need Help?

Questions? We can help
[Contact Us](#)



Where to Buy

Overview

Documents

3M™ Hot Melt Adhesive 3779 Q bonds to a variety of substrates and exhibits good fuel and oil resistance. See the applicator guide below for your dispensing options.

Specifications

Adhesive Type	Polyamide
Application Method	It is dispensed with 3M™ Scotch-Weld™ Hot Melt Applicator TC Q and EC
Bead Open Time	25 Second
Brand	3M
Color	Amber
Consumer Label	No
Container Volume	11 lb.
Heat Resistance	300 Degree Fahrenheit
Heat Resistance Range	High
Industries	Automotive , Construction , Furniture , Signage , Consumer Goods , Specialty Vehicle , Transportation , General Industrial , Military & Government , Retail , Electronics , Woodworking , Packaging
Length	8 Inch
Length (Metric)	0.2 m
Meets Specifications	UL 94 Listing VO
Open Time Range	Short
Product Form	Pound
Size	Q
Solids Weight Percent (Approximate)	100 Percent
Width	0.62 Inch
Width (Metric)	15.74 mm

– Accessories



3M™ Hot Melt Applicator EC, 1 per case



3M™ Hot Melt Applicator TC with Quadrack Converter and Palm Trigger, 1 per case

